

Datasheet JDW-10

Articlenumber: H530997

Differential pressure switch, 400...1600Pa, internal setting

Delivery without mounting bracket, can be screwed on directly (using 2 screws).



Ambient temperature, lower value	-15 °C
Ambient temperature, upper value	80 °C
Bearing temperature, lower value	15 °C
Bearing temperature, upper value	80 °C
Colour	Black
Control function, overpressure or underpressure	Yes
Control range, pressure (lower value)	400 Pa
Control range, pressure (upper value)	1600 Pa
Degree of contamination	2
Depth	46,5 mm
Electric connection	Screw terminals
Electronic version	No
External setting	No
Function type (systems engineering)	Monitor
Height	86 mm
Housing material	Plastic
Internal setting	Yes
Max.pressure	5000 Pa
Maximum air humidity (non-condensing)	95 % r.H

Maximum switching current	1,5 (0,4) AAC, 1 (0,2) ADC
Maximum switching voltage	230 V AC , 50 Hz / 24 V DC
Medium	Air, not aggressive
Medium temperature	-15 °C
Minimum switching current	1 mA
Minimum switching voltage	12 V AC, 50 Hz 12 V DC
Mounting / attachment	Wall mounting
Number of control ranges	1
Number of outputs	2
Operating voltage	None
Operation	Internal setpoint adjuster
Output signal	Switching
Potential free switching contact	Yes
Pressure connection	6,2 mm
Protection class	II, following appropriate mounting
Safety and EMC	In accordance with DIN EN 60730
Sensor element	Pressure membrane
Surface properties	Matt
Switching contact	Two-way contact
Switching difference	Approx. 30...60 Pa
Switching element	Microswitch
Switching power	345 WAC, 24 WDC
Type of protection	IP54
Width	90 mm
With explosion protection	No

