

HM100PR EHV SF₆ DENSITY MONITOR



> Description

These instruments are used to monitor SF₆ gas density in sealed tanks. They are applied to provide a signal outputs when the density reaches the set value. At the same time, they reliably output SF₆ gas density signal for remote monitoring. They are specifically designed for over 500KV EHV grade application field, adapting multi-level protection and full range of shielding measures to ensure the reliable operation of the products.

> Application

SF₆ Gas Insulated Switchgear (GIS) SF₆ Insulated Transformers
SF₆ Insulated Circuit Breakers SF₆ Insulated Mutual Inductor
SF₆ Insulated Pole-Mounted Switch SF₆ Insulated Busbar Systems

> Features

1. They adopt highly reliable protection circuit design, multi-level isolation and filtering technology, thus effectively inhibiting the intrusion of conductive interference.
2. They adopt the full-body shield design, stainless steel shielding shell, shielding junction box and military-grade shielding window glass, thus ensuring the ability of anti-electromagnetic radiation interference.
3. They are able to adopt the optic fiber communication backstage, thus avoiding data transmission link from electromagnetic interference.
4. The use of high-precision SF₆ density algorithm ensures that the background monitoring data coincides with those field instructions.
5. They are fully compatible with ordinary SF₆ remote products. They do not need other modifications in strong interference occasions.
6. The temperature compensation device ensures higher measurement accuracy.
7. Suitable for indoor or outdoor installation
8. Up to Four switch contacts can achieve overpressure alarm, dual alarm or double locking and many other solutions, ensuring the monitoring more secure and reliable

> Options

1. Power-frequency withstand voltage: 2.5kV 50/60 Hz 1min
2. Oil-filled
3. Measuring medium: SF₆, Air, N₂, SF₆ + N₂ and other gases

> Technical Data

1. Case diameter: 100mm	Cable size: 1.5mm ² recommended, 2.5mm ² maximum
2. Scale range: -0.1 to 0.9MPa (customizable)	10. Insulation properties:
3. Accuracy: (related to the measuring span; SF ₆ in gas phase)	Insulation resistance: >100 MΩ (DC 500 V)
a) At 20°C: Class 1.0 or 1.5	Withstand voltage: 2kV, 50/60 Hz 1 min
b) -40°C to +60°C: Class 2.5	11. Contact type: Magnetic snap-action contact
4. Degree of protection: IP65	80%Ag, 20%Ni, 10μm Au plated
5. Ambient conditions:	12. Impact rating: 50g (oil-filled), 30g (non-oil-filled)
-40°C to +60°C, relative humidity ≤95%RH	13. Contact electrical parameters: 30W/50VA, 1A (maximum)
6. Leakage rate: ≤ 1 × 10 ⁻⁹ Pa·m ³ /s (Helium leakage inspection)	220VDC/380V 50/60Hz (maximum)
7. Process connection: M20 × 1.5, (customizable)	14. Window glass: Laminated safety glass
8. Installation method: radial or axial	15. Weight: 1.2kg
9. Electrical connection: Plug-in connection M20 × 1.5 sealing head	16. Pressure element: Bourdon tubes

> Main electrical performance indicators and specifications of the remote transmission part

1. Power supply: DC 24V
2. Power consumption: < 2W
3. Communication mode: RS485
4. Protocol: ModBus RTU
5. Baud rate: 9600bps
6. Anti-electromagnetic interference:
 - IEC61000-4-2: level 4 /A (8KV/15kV)
 - IEC61000-4-3: Exceed national standard requirements /A (30V/m)
 - IEC61000-4-4: level 4/A (4KV)
 - IEC61000-4-5: level 4/A (+/-2Kv)
 - IEC61000-4-6: level 3/A (10V)
 - IEC61000-4-8: level 5/A (100A/m)
 - IEC61000-4-9: level 5/A (100 0A/m)
 - IEC61000-4-10: level 5/A (100A/m)
 - IEC61000-4-12: Exceed national standard requirements /A (4KV)
 - IEC61000-4-17: level 3/A (10%UN)
 - IEC61000-4-29: 0.1s/A (40%UT/70%UT)

> Dimensions

