

Datasheet RTKSA-000.100

Articlenumber: KA000000

Universal capillary thermostat, 0...50...°C, hysteresis 1.3K, TR, external setting



Ambient temperature, upper value	80 °C
Bearing temperature, lower value	-30 °C
Bearing temperature, upper value	80 °C
Capillary length	2 m
Colour	Anthr. grey (RAL7016), frontp. transp.
Contact interlocking	No
Control range, lower value	0 °C
Control range, upper value	50 °C
Cooling control function	Yes
Depth	66,7 mm
Device version	Surface-mounted unit
Diameter sensor element	6 mm
Electric connection	Push-in terminal
Electronic control	No
External setting	Yes
Function type (systems engineering)	TR
Heating control function	Yes
Height	146,8 mm
Internal setting	No
Length of sensor	175 mm

Max. sensor temperature	57 °C
Maximum air humidity (non-condensing)	95 % r.H
Maximum switching current	O: 16 (2,5) A; S: 6,3 (2,5) A, 0,25 ADC
Maximum switching voltage	230 V AC 50 / 60 Hz, 230 V DC
Minimum switching current	At 24 V (AC/DC) min. 100 mA
Minimum switching voltage	24 V AC / 50 Hz, 24 V DC
Mounting / attachment	In imm. sleeve, prot. coil, on tube, etc
Number of control ranges	1
Number of outputs	2
Operating voltage	None
Operation	Rotary knob
Output signal	Switching
Potential free switching contact	Yes
Protection class	I
Safety and EMC	In accordance with DIN EN 60730
Scale	Degree Celsius
Sensor element	Capillary tube
Sensor material	Cu
Switching contact	Two-way contact
Switching difference	1.3 K
Switching difference, can be adjusted	No
Switching element	Microswitch
Type of protection	IP40
Width	53 mm
With explosion protection	No

