



CAMPI SCALA

Pressione / Pressure

Bar	0÷1	0÷1,6	0÷2,5	0÷4	0÷6	0÷10	0÷16	0÷25	0÷40	0÷60	0÷100	0÷160	0÷250	0÷400	0÷600
Divisioni / Graduation	0,005	0,005	0,01	0,02	0,02	0,05	0,06	0,1	0,2	0,2	0,5	0,5	1	2	2
Numerazione / Numeration	0,1	0,1	0,2	0,2	0,5	1	1	2	2	5	10	10	20	20	50

Vuoto e manovutometri / Vacuum and compound

Bar	-1÷0
Divisioni / Graduation	0,005
Numerazione / Numeration	0,1

RANGES

Tipo 801CA: Montaggio diretto, raccordo radiale Type 801CA: Direct mounting, radial connection	Tipo 808CA: Montaggio a quadro, flangia a 3 fori anteriore, attacco post. centrale Type 808CA: Panel mounting, 3 hole front flange, rear central connection	Tipo 810CA: Montaggio a quadro, staffa ad "U" posteriore, attacco post. eccentrico Type 810CA: Panel mounting, "U" type rear bracket, rear eccentric connection	Tipo 807CA: Montaggio a quadro, flangia a 3 fori anteriore, attacco post. eccentrico Type 807CA: Panel mounting, 3 hole front flange, rear eccentric connection
---	--	--	--

Tipo Type	DN/DS	b	D	E	H	N	L	S
801CA	150/6"	54	150	163	125	-	-	-
807CA	150/6"	54	150	163	-	89	168	196
808CA	150/6"	54	150	163	-	89	168	196
810CA	150/6"	54	150	163	-	89	-	-

OPZIONI ED ACCESSORI

- Astuccio per il trasporto
- Cassa in AISI 316
- Valvola ANCC
- Scale in kg/cm²
- Trasparente in vetro di sicurezza sp. 4 mm
- Versione a FRONTE SOLIDO.

OPTIONS AND ACCESSORIES

- Carrying case
- Case in st. st. 316
- ANCC valve
- Scale in kg/cm²
- Safety glass type thickness 4 mm
- SOLID FRONT execution.

COME ORDINARE: Prego specificare: modello, campo scala, tipo e dimensioni filettatura attacco, eventuali opzioni o certificazione SIT.
Esempio: modello MB801CA, 0/25Bar, ½"NPTM

HOW TO ORDER: Please specify: model, range, type and dimensions connection, options or SIT certification if any.
Example: model MB801CA, 0/25Bar, ½"NPTM